



Final Strip H.D.TM

HEAVY DUTY FLOOR STRIPPER



An economical floor stripper, **Final Strip H.D.** is a powerful, non-ammoniated butyl-based formula that cuts through heavy build-up and hard to remove water-based sealers in record time.

DIRECTIONS

Read all directions and Safety Data Sheets (SDS) before using.

- Mix stripper with cold water per the following dilutions:
 Heavy coating removal: 1:4 (32 US oz per gallon/250 ml per 1 liter of water).
 Normal coating removal: 1:6 (21.5 US oz per gallon/166 ml per 1 liter of water).
 Light coating removal: 1:8 (16 US oz per gallon / 125 ml per 1 liter of water).
- Apply solution liberally to the floor and allow to soak for 10 minutes ensuring the solution does not dry.
- Scrub floor with automatic scrubber or stripping machine. Pick up dirty solution with automatic scrubber or wet vac.
- Rinse thoroughly with clean water and allow floor to dry completely before applying any finish.

Note: Test floor for color fastness in an inconspicuous area.

PRODUCT INFO

Product Code	502FS	502FSE	502MP	502MPE
Volume	2.50 US gallons	10 liters	1.06 US gallons	4 liters
Shipping Package	2 x 2.5 gallons	2 x 10 liters	4 x 1.06 gallons	4 x 4 liters
Pallet Quantity	48	48	48	48

SURFACES



TECHNICAL DATA

Description	Non-ammoniated, ultra high performance stripper
Appearance	Clear red liquid
Viscosity (Brookfield) @ 68°F (20°C)	<5 centipoise
Flash Point ASTM D56-05 (2010)	158°F (70°C)
VOC 40 CFR Part 59 Subpart C	33% (as supplied) 2.94% (1:10) 3.59% (1:8) 6.48% (1:4)
Fragrance	Slight lemon
Shelf Life ASTM D1791-93 (2008)	2 years
Density ASTM D1475-98 (2008)	8.3 lb/gal @ 68°F 0.99 kg/L @ 20°C
Container	2.5 US gal/9.5 L (FS packaging) 2.64 US gal/10 L (FSE packaging) 1.06 US gal/4 L (MP packaging) 1.06 US gal/4 L (MPE packaging)

